



**NOTES**

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS SHOWN OTHERWISE.
2. CONCRETE STRENGTH GRADE - N25.
3. IF POWER SUPPLY POINT IS NOT EARTHED: PROVIDE 50 DIA PVC CONDUIT AND 20 NB GI PIPE EARTHSTAKE.
4. CONTROLLER WILL BE LOCATED AND ORIENTED AS SHOWN ON DRAWINGS AND AS AGREED ON SITE BY THE SUPERINTENDENT.
5. PROVIDE CONCRETE APRON IN UNPAVED LOCATIONS.

15/03/2010 4:02:02 PM X:\CIVIL STANDARD DRAWINGS\TRAFFIC 6 - CS1500 SERIES STANDARDS\CS1503-3.dgn

3.	GOVERNMENT DEPARTMENT LOGOS CHANGED.	3/2010	W.L.
2.	NOTES UPDATED.	7/2004	K.S.
1.	GOVERNMENT DEPARTMENT LOGOS CHANGED.	5/2002	K.S.
No.	DESCRIPTION	DATE	INIT.
AMENDMENTS			

**WARNING**  
**BEWARE OF UNDERGROUND SERVICES**  
 The locations of underground services are approximate only and their exact position should be proven on site. No guarantee is given that all existing services are shown.

DRAWN	K. SCHULZE	CHECKED	
DATE	1-9-1992	DATE	
DESIGNED		CHECKED	
DATE		DATE	
DESIGN PROJECT LEADER	<i>[Signature]</i>	PROJECT OFFICER	
DATE	JULY 2004	DATE	

**Northern Territory Government**

Department of Construction and Infrastructure

STANDARD DRAWING SIGNAL DETAILS CONTROLLER FOUNDATION				
FILE No.	ASSET No.	SHEET No.	DRAWING No.	AMEND.
		1 OF 1	CS1503-3	
				SHEET SIZE A3