


# Safety Barrier Technical Conditions for Use

## Trend Median Terminal - Permanent

	<b>Issue Date:</b> 24 March 2023	<b>Proponent:</b> Ingal Civil Products
	<p><b>These conditions take precedence over any instructions in the Product Manual.</b></p> <p>This document is a summary of the Austroads Safety Barrier Assessment Panel's assessment of the technical performance of the product against AS/NZS 3845 Parts 1 or 2 only. It does not consider procurement practices by individual Road Agencies.</p> <p>The Austroads Safety Assessment Panel may at any time, withdraw or modify this Technical Conditions for Use without notice.</p> <p>These acceptance conditions should be read in conjunction with the Product Manual and Austroads Guide to Road Design Part 6: Roadside Design, Safety and Barriers.</p> <p>Acceptance of this product does not place any obligation on the Northern Territory Government or its contractors, to purchase or use the product.</p>	

Status	<b>Accepted – may be used on the classified road network</b>
Product accepted	<p>Trend Median Terminal</p> <p><u>Variants</u></p> <p>Variants that are NOT listed above are NOT recommended for acceptance.</p>
Accepted Impact Speed	100 km/h (TL3)
Product Manual reviewed	Release 02/22b
Product Manual	<a href="#">MASH Guardrail End Terminals   Ingal Civil Products - Australia</a>

## Design Requirements

Containment Level	Point of Redirection		Tested Article Length (m)	Anchor/Post Spacing (m)	Notes
	Leading (m)	Trailing (m)			
MASH TL3	Post #3	Post #3	11.10	1.905	Clear run out area required

## Approved Connections

<i>An accepted end treatment must be provided at both ends of all barrier installations</i>	
<b>Public Domain Products</b>	
W-Beam Guardrail	Permitted
Thrie-Beam Guardrail	Permitted
Concrete	Not permitted
<b>Proprietary Products</b>	
	Refer to safety barrier Technical Conditions for Use for accepted proprietary connections.

## Design Guidance

Minimum installation length (m)	11.10
System width (m)	0.73
Slope limit	10%
Systems conditions	Installation on top of a kerb is not recommended, however if installed on top of a kerb all system components must be free to operate.
Gore area use	Not permitted
Pedestrian area use	Permitted
Cycleway use	Permitted
Frequent impact likely	Permitted
Remote location	Permitted
Median use	Permitted

Foundation Pavement Conditions					
Pavement Type	Use	Max Accepted Impact Speed (km/h)	Post/Pin Spacing (m)	Post/Pin Type	Pavement Construction
Concrete	Not Permitted				
Deep lift asphaltic concrete					
Asphaltic concrete over granular pavement	Permitted	100	1.905	Refer to drawings	Minimum AASHTO standard soil strength
Flush seal over granular pavement					
Unsealed compacted formation					

**Note:** Installation in pavement conditions not permitted above have not been justified to the Panel's satisfaction.